

# RIMSLOW SERIES

FOR TEXTILE PRE-TREATMENT AND POST-TREATMENT

## A COMPLETE LINE OF TEXTILE PRE-TREATMENT AND POST-TREATMENT MACHINES

### COATING



**TR300-1850C**  
Up to 75Lm/h

### STEAMING




**TR300-1850S**  
Up to 55Lm/h



**TR600-1850S**  
Up to 260Lm/h

### WASHING



**TR600-1850W**  
Up to 130Lm/h

## CHOOSE THE SET THAT BENEFITS YOU THE MOST

DIRECT SUBLIMATION  
STARTING SET



**Coating**  
TR300-1850C



**Printing**  
TX300P or TX500 or Tiger

Starting set with direct sublimation (4C or 6C).

※An optional washing machine for direct sublimation.



**Washing**  
TR600-1850W


TEXTILE PIGMENT  
STARTING SET



**Coating**  
TR300-1850C



**Printing**  
TX300P-1800B



**Steaming**  
TR300-1850S

Starting set with textile pigment inks (4C or 7C).

REACTIVE / ACID /  
DISPERSE  
COMPACT SET



**Coating/Washing**  
TR600-1850W



**Printing**  
TX300P-B or TX500B or Tiger



**Steaming**  
TR300/600-1850S

Compact starting set for smaller production with the versatile TR600-1850W used for both coating and washing.

REACTIVE / ACID /  
DISPERSE  
FULL SET




**Coating**  
TR300-1850C



**Printing**  
TX300P-B or TX500B or Tiger



**Steaming**  
TR300/600-1850S



**Washing**  
TR600-1850W

Full-line production starting set for reactive, disperse or acid dye inks

## INK AND CORRESPONDING PRE-TREATMENT MACHINE FOR CONSISTENT RESULTS

We develop our pre-treatment machines for you to get the best out of our inks. Colour matching is facilitated in order to achieve steady colour results, even when they come from different production points or printing and post-processing facilities.

## COLOURING TEST BEFORE THE PRODUCTION RUN

With the introduction of the new textile production line of pre-treatment, printing, and post-treatment machines, Mimaki can also conduct colouring tests adapted to your requirements. The colouring test makes sure you can start your production smoothly, as soon as the production line is set, without testing delay.

## ONE-STOP SOURCE FOR YOUR TEXTILE PRODUCTION

By choosing your textile production line from Mimaki, you will need only one contact to assist you with any point of the production line, making sure it is in consistence with the preceeding or following step. From the printer to the coating and washing machines, everything is covered by one support service, for your peace of mind. With vast global network of long-established partners and unparalleled textile printing heritage, Mimaki is here to support your business from start to finish.

## PRODUCT LINE-UP

TYPE	Coating	Steaming		Washing / Coating
PRODUCT	TR300-1850C	TR300-1850S	TR600-1850C	TR600-1850W
MEDIA WIDTH	1,850mm			
PRODUCTION SPEED	75Lm/h	Acid dye ink (102°C/30min) 12 Lm/h Reactive dye ink (102°C/10min) 33 Lm/h Disperse dye ink (160-180°C/6min) 55 Lm/h Pigment ink (130-160°C/6min) 55 Lm/h	Acid dye ink (102°C/30min) 52 Lm/h Reactive dye ink (102°C/10min) 155 Lm/h Disperse dye ink (160-180°C/6min) 260 Lm/h Pigment ink (130-160°C/6min) 260 Lm/h	130Lm/h
TEMPERATURE	125°C	180°C		180°C
WATER TANK	50L	25L	50L	25L (Pre-treatment) 340L x 2 (Washing)
HEATER TYPE	Electric			
DIMENSION (WxDxH)	2.6 x 1.7 x 1.1m	2.5 x 1.6 x 1.3m	2.6 x 2.9 x 1.6m	2.7 x 4.8 x 2.4m

Specifications, design and dimensions stated in this folder may be subject to change without notice (for technical improvements, etc.) •

The corporate and merchandise names written on this folder are the trademark of the respective corporations • Inkjet printers print using extreme fine dots, so colours may vary after replacement of the printing heads, also note that if using multiple printer unites, colours could vary slightly from one unit to other unit due to slight individual differences • Compositor's errors reserved

[www.mimakieurope.com](http://www.mimakieurope.com)